

Description

Diameter: 13/64", steel comp 302 band or steel corrosion resisting band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715C14TW
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-369-1411
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N NAS1715C14TW Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Any Acceptable
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.913 Inches Minimum And 0.943 Inches Maximum
Distance From Loop Center To Tongue End:	1.132 Inches Minimum And 1.162 Inches Maximum
Loop Inside Diameter:	0.860 Inches Minimum And 0.890 Inches Maximum
Special Features:	W/sodium Treated Cushion
Material:	Plastic Cushion
Material:	Steel Comp 302 Band Or Steel Corrosion Resisting Band
Material Document And Classification:	Ams 3651 Assn Std Single Material Response Cushion
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount
Specification/standard Data:	80205-nas1715 Professional/industrial Association Standard

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C14TW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.