

Description

Diameter: 13/64", steel comp 302 band or steel corrosion resisting band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1715C15K |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-500-2111 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1715C15K Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.051 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 0.944 Inches Minimum And 0.974 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.163 Inches Minimum And 1.193 Inches Maximum |
| Loop Inside Diameter: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Material: | Plastic Cushion |
| Material: | Steel Comp 302 Band Or Steel Corrosion Resisting Band |
| Material Document And Classification: | Ams 3651 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721,comp Ti 321 Mil Spec 2nd Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Specification/standard Data: | 80205-nas1715 Professional/industrial Association Standard |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C15K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.