



Military-Fasteners.com

P/N NAS1715C21Z

Description


Diameter: 13/64", steel comp 302 band or steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | NAS1715C21Z |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5340-01-413-8551 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N NAS1715C21Z Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.051 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.131 Inches Minimum And 1.161 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.340 Inches Minimum And 1.380 Inches Maximum |
| Loop Inside Diameter: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Environmental Attribute Code: | Asbestos Alternative Products |
| Material: | Glass Fiber Cushion |
| Material: | Steel Comp 302 Band Or Steel Comp 321 Band |
| Material Document And Classification: | Ams 3677 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Specification/standard Data: | 80205-nas1715 Professional/industrial Association Standard |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C21Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.