

Description

Cushioned Loop Clamp part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1715C2N |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-597-9522 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1715C2N Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.484 Inches Minimum And 0.516 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.025 Inches Minimum And 0.037 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.452 Inches Minimum And 0.462 Inches Maximum |
| Distance From Loop Center To Tongue End: | 0.670 Inches Minimum And 0.680 Inches Maximum |
| Loop Inside Diameter: | 0.250 Inches Nominal |
| Material: | Rubber Synthetic Cushion |
| Material: | Steel Comp 4130 Band |
| Material Document And Classification: | Ams 6350 Assn Std Single Material Response Band |
| Surface Treatment: | Cadmium Band |
| Style Designator: | Offset Mount |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C2N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.