

**Description**

Diameter: 13/64", steel comp 321 band or steel comp 302 band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1715C3K
Minimum Qty (MOQ):	10
NSN:	5340-00-570-0435
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1715C3K Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.481 Inches Minimum And 0.511 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.700 Inches Minimum And 0.730 Inches Maximum
<b>Loop Inside Diameter:</b>	0.188 Inches Nominal
<b>Material:</b>	Plastic Polytetrafluoroethylene Cushion
<b>Material:</b>	Steel Comp 321 Band Or Steel Comp 302 Band
<b>Material Document And Classification:</b>	Ams3840 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Band Or Mil-s-5059 Mil Spec 2nd Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount
<b>Specification/standard Data:</b>	80205-nas1715 Professional/industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C3K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.