

**Description**

Diameter: 13/64", steel comp 321 band or steel comp 347 band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1715C7KW
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-096-2880
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1715C7KW Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat
<b>Overall Width:</b>	0.375 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.0285 Inches Minimum And 0.0355 Inches Maximum
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.623 Inches Nominal
<b>Distance From Loop Center To Tongue End:</b>	0.811 Inches Nominal
<b>Loop Inside Diameter:</b>	0.423 Inches Minimum And 0.453 Inches Maximum
<b>Material:</b>	Plastic Cushion
<b>Material:</b>	Steel Comp 321 Band Or Steel Comp 347 Band
<b>Material Document And Classification:</b>	L-p-403 Fed Spec Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec All Material Responses Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C7KW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.