

**Description**

Diameter: 13/64", steel comp 302 band or steel corrosion resisting band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | NAS1715C9K                  |
| Minimum Qty (MOQ):      | 10 EA                       |
| NSN:                    | 5340-01-043-7944            |
| Schedule B:             | 7318.29.0000                |
| ECCN:                   | 9A991                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE  
AVAILABLE

## P/N NAS1715C9K Specifications

|                                                                  |                                                                                                  |
|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Tongue Hole Type:</b>                                         | Round, Unthreaded                                                                                |
| <b>Cushioning Environmental Protection:</b>                      | Heat                                                                                             |
| <b>Overall Width:</b>                                            | 0.500 Inches Nominal                                                                             |
| <b>Diameter:</b>                                                 | 0.204 Inches Nominal                                                                             |
| <b>Material Thickness:</b>                                       | 0.032 Inches Nominal                                                                             |
| <b>Center To Center Distance Between Loop And Mounting Hole:</b> | 0.668 Inches Minimum And 0.698 Inches Maximum                                                    |
| <b>Distance From Loop Center To Tongue End:</b>                  | 0.887 Inches Minimum And 0.917 Inches Maximum                                                    |
| <b>Loop Inside Diameter:</b>                                     | 0.547 Inches Minimum And 0.577 Inches Maximum                                                    |
| <b>Material:</b>                                                 | Plastic Cushion                                                                                  |
| <b>Material:</b>                                                 | Steel Comp 302 Band Or Steel Corrosion Resisting Band                                            |
| <b>Material Document And Classification:</b>                     | Ams 3651 Assn Std Single Material Response Cushion                                               |
| <b>Material Document And Classification:</b>                     | Mil-s-5059 Mil Spec 1st Material Response Band Or Mil-s-6721 Mil Spec 2nd Material Response Band |
| <b>Surface Treatment:</b>                                        | Passivate Band                                                                                   |
| <b>Surface Treatment Document And Classification:</b>            | Qq-p-35 Fed Spec Single Treatment Response Band                                                  |
| <b>Style Designator:</b>                                         | Offset Mount                                                                                     |
| <b>Specification/standard Data:</b>                              | 80205-nas1715 Professional/industrial Association Standard                                       |

## How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715C9K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.