

## **P/N NAS1715D10T**

### **Description**

Diameter: 13/64", plastic polytetrafluoroethylene cushion

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1715D10T
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-513-4759
Schedule B:	7616.10.9090
FCCN:	94991



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1715D10T Specifications**

Tongue Hole Type:	Round, Unthreaded
Temp Rating:	500.0 Deg Fahrenheit
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.700 Inches Minimum And 0.730 Inches Maximum
Distance From Loop Center To Tongue End:	0.925 Inches Minimum And 0.954 Inches Maximum
Loop Inside Diameter:	0.625 Inches Nominal
Special Features:	Ptfe Cushion Is Sodium Treated
Material:	Aluminum Alloy 2024 Band
Material:	Plastic Polytetrafluoroethylene Cushion
Material Document And Classification:	Ams3660 Assn Std Single Material Response Cushion Or Ams3652 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Cond T4/t42 Fed Spec 1st Material Response Band
Style Designator:	Offset Mount
Specification/standard Data:	80205-nas1715 Professional/industrial Association Standard

## **How to Order**

Order this cushioned loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1715D10T">https://military-fasteners.com/clamps/loop+clamps/NAS1715D10T</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.