

**Description**

Diameter: 13/64", plastic polytetrafluoroethylene cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1715D10T
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-513-4759
Schedule B:	7616.10.9090
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1715D10T Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Temp Rating:</b>	500.0 Deg Fahrenheit
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.700 Inches Minimum And 0.730 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.925 Inches Minimum And 0.954 Inches Maximum
<b>Loop Inside Diameter:</b>	0.625 Inches Nominal
<b>Special Features:</b>	Ptfe Cushion Is Sodium Treated
<b>Material:</b>	Aluminum Alloy 2024 Band
<b>Material:</b>	Plastic Polytetrafluoroethylene Cushion
<b>Material Document And Classification:</b>	Ams3660 Assn Std Single Material Response Cushion Or Ams3652 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Qq-a-250/5 Cond T4/t42 Fed Spec 1st Material Response Band
<b>Style Designator:</b>	Offset Mount
<b>Specification/standard Data:</b>	80205-nas1715 Professional/industrial Association Standard

## How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715D10T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.