

Description

Diameter: 13/64", plastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | NAS1715D24KWX |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-00-493-7020 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N NAS1715D24KWX Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Any Acceptable |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.058 Inches Minimum And 0.068 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 1.249 Inches Nominal |
| Distance From Loop Center To Tongue End: | 1.452 Inches Minimum And 1.482 Inches Maximum |
| Loop Inside Diameter: | 1.500 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Plastic Polytetrafluoroethylene Cushion |
| Material Document And Classification: | Qq-a-250/5,t4 Fed Spec Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715D24KWX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.