

## **P/N NAS1715D24KWX**

### **Description**

Diameter: 13/64", plastic polytetrafluoroethylene cushion

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1715D24KWX

Minimum Qty (MOQ): 5 EA

NSN: 5340-00-493-7020

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1715D24KWX Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Any Acceptable
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	1.249 Inches Nominal
Distance From Loop Center To Tongue End:	1.452 Inches Minimum And 1.482 Inches Maximum
Loop Inside Diameter:	1.500 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Plastic Polytetrafluoroethylene Cushion
Material Document And Classification:	Qq-a-250/5,t4 Fed Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

## **How to Order**

Order this cushioned loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1715D24KWX">https://military-fasteners.com/clamps/loop+clamps/NAS1715D24KWX</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1715D24KWX">https://military-fasteners.com/clamps/loop+clamps/NAS1715D24KWX</a> and selecting the