

Description

Diameter: 13/64", rubber chloroprene class cr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715D3N
Minimum Qty (MOQ):	30 EA
NSN:	5340-01-176-4058
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1715D3N Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat And Oil Resistant And Weather Resistant
Overall Width:	0.484 Inches Minimum And 0.516 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.025 Inches Minimum And 0.037 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	0.488 Inches Minimum And 0.508 Inches Maximum
Distance From Loop Center To Tongue End:	0.716 Inches Nominal
Loop Inside Diameter:	0.312 Inches Nominal
Material:	Aluminum Alloy 2024 Band And Aluminum Alloy 1230 Band
Material:	Rubber Chloroprene Class Cr Cushion
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams 4041 Assn Std All Material Responses Band
Style Designator:	Offset Mount

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715D3N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.