P/N NAS1715D3S

Description

Diameter: 13/64", rubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715D3S
Minimum Qty (MOQ):	20
NSN:	5340-00-128-7426
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE AVAILABLE

* See page 2 for technical characteristics

P/N NAS1715D3S Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat And Oil Resistant And Weather Resistant
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.481 Inches Minimum And 0.511 Inches Maximum
Distance From Loop Center To Tongue End:	0.700 Inches Minimum And 0.730 Inches Maximum
Loop Inside Diameter:	0.173 Inches Minimum And 0.203 Inches Maximum
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Ams 3226 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-25015 T4 Or T42 Fed Spec Single Material Response Band
Style Designator:	Offset Mount
Specification/standard Data:	80205-nas1715 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1715D3S and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.