

Description

Diameter: 13/64", plastic polytetrafluoroethylene cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715D6T
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-284-2563
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N NAS1715D6T Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.574 Inches Minimum And 0.604 Inches Maximum
Distance From Loop Center To Tongue End:	0.808 Inches Nominal
Loop Inside Diameter:	0.360 Inches Minimum And 0.390 Inches Maximum
Material:	Aluminum Alloy 2024 Band And Aluminum Alloy 1230 Band
Material:	Plastic Polytetrafluoroethylene Cushion
Material Document And Classification:	Ams 3651 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5,t4 Or T42 Fed Spec All Material Responses Band
Style Designator:	Offset Mount
Specification/standard Data:	80205-nas1715 Professional/industrial Association Standard

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715D6T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.