

Description

Diameter: 17/64", rubber chloroprene class cr cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1715D9NH
Minimum Qty (MOQ):	1 EA
NSN:	5340-01-083-6694
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

# P/N NAS1715D9NH Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat And Oil Resistant And Weather Resistant
<b>Overall Width:</b>	0.484 Inches Minimum And 0.516 Inches Maximum
<b>Diameter:</b>	0.260 Inches Minimum And 0.270 Inches Maximum
<b>Material Thickness:</b>	0.045 Inches Minimum And 0.057 Inches Maximum
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	0.742 Inches Minimum And 0.762 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	0.970 Inches Nominal
<b>Loop Inside Diameter:</b>	0.688 Inches Nominal
<b>Material:</b>	Aluminum Alloy 2024 Band
<b>Material:</b>	Rubber Chloroprene Class Cr Cushion
<b>Material Document And Classification:</b>	Ams 3209 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Ams 4041 Assn Std Single Material Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1715D9NH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.