

## Description

Length: 1-61/64", saddle style, NAS1716 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model: NAS1716C12K

Minimum Qty (MOQ): 5

NSN: 5340-01-020-5585

Schedule B: 7318.29.0000

ECCN: 9A991

National Motor Freight: 095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1716C12K Specifications

<b>Overall Length:</b>	1.938 Inches Minimum And 1.968 Inches Maximum
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Material Thickness:</b>	0.040 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	1.502 Inches Minimum And 1.532 Inches Maximum
<b>Cushioning Material:</b>	Plastic, Ams 3651
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	0.859 Inches Minimum And 0.889 Inches Maximum
<b>Inside Diameter/arch Length:</b>	0.735 Inches Minimum And 0.765 Inches Maximum
<b>Material:</b>	Steel, Mil-s-5059, Comp 302 Or Steel, Mil-s-6721, Comp 321
<b>Material:</b>	Steel Comp 302 Or Steel Comp 321
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Saddle Arch
<b>Surface Treatment:</b>	Passivated, Qq-p-35
<b>Specification/standard Data:</b>	80205-nas1716 Professional/industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C12K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.