

Description

Length: 1-15/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1716C12T
Minimum Qty (MOQ):	5
NSN:	5340-01-119-3980
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1716C12T Specifications

Overall Length:	1.953 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Distance Between Mounting Hole Centers:	1.502 Inches Minimum And 1.532 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.874 Inches Nominal
Inside Diameter/arch Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Mil-s-6721, Comp 321
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1716 Professional/Industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C12T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.