

Description

Length: 2-9/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1716C15K |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-034-2896 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS1716C15K Specifications

| | |
|--|---|
| Overall Length: | 2.141 Inches Nominal |
| Overall Width: | 0.500 Inches Nominal |
| Material Thickness: | 0.040 Inches Nominal |
| Distance Between Mounting Hole Centers: | 1.690 Inches Minimum And 1.720 Inches Maximum |
| Cushioning Material: | Plastic, Ams 3651 |
| Cushion: | Included |
| Mounting Pad: | Not Included |
| Mounting Hole Size: | 0.204 Inches Nominal |
| Distance Between Base And Inside Of Arch: | 1.040 Inches Nominal |
| Inside Diameter/arch Length: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Material: | Steel, Mil-s-5059, Comp 302, Annealed Or Steel, Mil-s-6721, Comp Ti 321 |
| Material: | Steel Comp 302 Or Steel Comp 321 |
| Surface Treatment: | Passivate |
| Style Designator: | Saddle Arch |
| Surface Treatment: | Passivated, Qq-p-35 |
| Specification/standard Data: | 80205-nas1716 Professional/industrial Association Standard |

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C15K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.