

Description

Length: 2-13/64",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716C16K
Minimum Qty (MOQ):	5
NSN:	5340-00-151-5902
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N NAS1716C16K Specifications

Overall Length:	2.188 Inches Minimum And 2.218 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Distance Between Mounting Hole Centers:	1.752 Inches Minimum And 1.782 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.087 Inches Minimum And 1.117 Inches Maximum
Inside Diameter/arch Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Material:	Steel
Material:	Steel
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C16K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.