

## **P/N NAS1716C22K**

### **Description**

Length: 2-21/32

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1716C22K

Minimum Qty (MOQ):

NSN: 5340-01-504-5484

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1716C22K Specifications**

Overall Length:	2.664 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.082 Inches Nominal
Distance From Loop Center To Tongue End:	1.332 Inches Nominal
Loop Inside Diameter:	1.375 Inches Nominal
Material:	Plastic Polytetrafluoroethylene Cushion
Material:	Steel Comp 304 Band Or Steel Comp 302 Band Or Steel Comp 321 Band
Style Designator:	Saddle Mount

## **How to Order**

Order this loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K">https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K">https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K">https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K">https://military-fasteners.com/clamps/loop+clamps/NAS1716C22K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/nas1716C22K">https://military-fasteners.com/clamps/nas1716C22K</a> and selecting the property of the proper