

Description

Length: 2-25/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1716C24K

Minimum Qty (MOQ): 5

NSN: 5340-01-116-1626

Schedule B: 7318.29.0000

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1716C24K Specifications

Overall Length:	2.789 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.289 Inches Nominal
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.624 Inches Nominal
Inside Diameter/arch Length:	1.485 Inches Minimum And 1.515 Inches Maximum
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Mil-s-6721, Comp 321
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C24K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.