

**Description**

Length: 2-29/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716C26K
Minimum Qty (MOQ):	1 EA
NSN:	5340-01-440-7679
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1716C26K Specifications

<b>Overall Length:</b>	2.9140 Inches Nominal
<b>Overall Width:</b>	0.6200 Inches Nominal
<b>Material Thickness:</b>	0.0620 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	2.3910 Inches Minimum And 2.4290 Inches Maximum
<b>Cushioning Material:</b>	Plastic, Polytetrafluoroethylene
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.2040 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	1.6870 Inches Nominal
<b>Inside Diameter/arch Length:</b>	1.6870 Inches Nominal
<b>Special Features:</b>	The Cushion Material Is Made To Ams 3660
<b>Material:</b>	Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510
<b>Material:</b>	Steel Comp 302 Or Steel Comp 321
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Saddle Arch
<b>Surface Treatment:</b>	Passivated, Qq-p-35

## How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C26K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.