

P/N NAS1716C26K

Description

Length: 2-29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1716C26K

Minimum Qty (MOQ): 1 EA

NSN: 5340-01-440-7679

Schedule B: 7616.99.5090

ECCN: 9A991

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip



^{*} See page 2 for technical characteristics

P/N NAS1716C26K Specifications

Overall Length:	2.9140 Inches Nominal
Overall Width:	0.6200 Inches Nominal
Material Thickness:	0.0620 Inches Nominal
Distance Between Mounting Hole Centers:	2.3910 Inches Minimum And 2.4290 Inches Maximum
Cushioning Material:	Plastic, Polytetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.2040 Inches Nominal
Distance Between Base And Inside Of Arch:	1.6870 Inches Nominal
Inside Diameter/arch Length:	1.6870 Inches Nominal
Special Features:	The Cushion Material Is Made To Ams 3660
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1716C26K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.