

P/N NAS1716C26K

Description

Length: 2-29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1716C26K

Minimum Qty (MOQ): 1 EA

NSN: 5340-01-440-7679

Schedule B: 7616.99.5090

ECCN: 9A991

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip



^{*} See page 2 for technical characteristics

P/N NAS1716C26K Specifications

| Overall Length: | 2.9140 Inches Nominal |
|---|---|
| - | |
| Overall Width: | 0.6200 Inches Nominal |
| Material Thickness: | 0.0620 Inches Nominal |
| Distance Between Mounting Hole Centers: | 2.3910 Inches Minimum And 2.4290 Inches Maximum |
| Cushioning Material: | Plastic, Polytetrafluoroethylene |
| Cushion: | Included |
| Mounting Pad: | Not Included |
| Mounting Hole Size: | 0.2040 Inches Nominal |
| Distance Between Base And Inside Of Arch: | 1.6870 Inches Nominal |
| Inside Diameter/arch Length: | 1.6870 Inches Nominal |
| Special Features: | The Cushion Material Is Made To Ams 3660 |
| Material: | Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510 |
| Material: | Steel Comp 302 Or Steel Comp 321 |
| Surface Treatment: | Passivate |
| Style Designator: | Saddle Arch |
| Surface Treatment: | Passivated, Qq-p-35 |

How to Order

Order this clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1716C26K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.