

## **P/N NAS1716C32K**

### **Description**

Length: 3-9/32",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1716C32K

Minimum Qty (MOQ): 5

NSN: 5340-01-473-8349

Schedule B: 7318.29.0000

ECCN: EAR99

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1716C32K Specifications**

Overall Length:	3.289 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.789 Inches Nominal
Cushioning Material:	Plastic, Polytetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	2.139 Inches Nominal
Inside Diameter/arch Length:	1.985 Inches Minimum And 2.015 Inches Maximum
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Mil-s-6721, Comp 321
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

## **How to Order**

Order this loop clamp from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/NAS1716C32K">https://military-fasteners.com/clamps/loop+clamps/NAS1716C32K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.