

**Description**

Length: 3-51/64", NAS1716 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | NAS1716C40K                 |
| Minimum Qty (MOQ):      | 5                           |
| NSN:                    | 5340-01-084-8532            |
| Schedule B:             | 7318.29.0000                |
| ECCN:                   | 9A991                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



\* See page 2 for technical characteristics

## P/N NAS1716C40K Specifications

|  |  |
|--|--|
| <b>Overall Length:</b>                           | 3.774 Inches Minimum And 3.804 Inches Maximum              |
| <b>Overall Width:</b>                            | 0.620 Inches Nominal                                       |
| <b>Material Thickness:</b>                       | 0.062 Inches Nominal                                       |
| <b>Distance Between Mounting Hole Centers:</b>   | 3.274 Inches Minimum And 3.304 Inches Maximum              |
| <b>Cushioning Material:</b>                      | Plastic, Ams 3651  |
| <b>Cushion:</b>                                  | Included   |
| <b>Mounting Pad:</b>                             | Not Included   |
| <b>Mounting Hole Size:</b>                       | 0.204 Inches Nominal                                       |
| <b>Distance Between Base And Inside Of Arch:</b> | 2.624 Inches Nominal                                       |
| <b>Inside Diameter/arch Length:</b>              | 2.485 Inches Minimum And 2.515 Inches Maximum              |
| <b>Material:</b>                                 | Steel, Mil-s-5059, Comp 302 Or Steel, Mil-s-6721, Comp 321 |
| <b>Material:</b>                                 | Steel Comp 302 Or Steel Comp 321                           |
| <b>Surface Treatment:</b>                        | Passivate  |
| <b>Style Designator:</b>                         | Saddle Arch  |
| <b>Surface Treatment:</b>                        | Passivated, Qq-p-35  |
| <b>Specification/standard Data:</b>              | 80205-nas1716 Professional/Industrial Association Standard |

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C40K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.