

Description

Length: 4-25/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716C56Z
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-408-1832
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1716C56Z Specifications

Overall Length:	4.789 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	4.274 Inches Minimum And 4.304 Inches Maximum
Cushioning Material:	Fabric, Ams3677
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	3.624 Inches Nominal
Inside Diameter/arch Length:	3.485 Inches Minimum And 3.515 Inches Maximum
Material:	Steel, Ams 5510 Or Steel, Mil-s-5059, Comp 302
Material:	Steel Comp 321 Or Steel Comp 302
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1716 Professional/Industrial Association Standard

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C56Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.