

Description

Length: 1-1/2", NAS1716 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1716C6K
Minimum Qty (MOQ):	5
NSN:	5340-01-166-6944
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS1716C6K Specifications

Overall Length:	1.562 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Distance Between Mounting Hole Centers:	1.111 Inches Minimum And 1.141 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.439 Inches Nominal
Inside Diameter/arch Length:	0.360 Inches Minimum And 0.390 Inches Maximum
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Saddle Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C6K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.