

Description

Length: 1-11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716C8T
Minimum Qty (MOQ):	1 EA
NSN:	5340-00-533-9321
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1716C8T Specifications

Overall Length:	1.672 Inches Minimum And 1.702 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Distance Between Mounting Hole Centers:	1.236 Inches Minimum And 1.266 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.517 Inches Minimum And 0.547 Inches Maximum
Inside Diameter/arch Length:	0.500 Inches Nominal
Material:	Cres Mil-s-5059 Comp 302 Or Cres Mil-s-6721 Comp Ti/321/
Material:	Cres Mil-s-5059 Comp 302 Or Cres Mil-s-6721 Comp Ti/321/
Surface Treatment:	Passivate,qq-p-35
Style Designator:	Saddle Arch
Surface Treatment:	Passivate,qq-p-35
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716C8T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.