

Description

Clamp part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1716D10T
Minimum Qty (MOQ):	1 EA
NSN:	5340-00-545-6874
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



P/N NAS1716D10T Specifications

Overall Length:	1.813 Inches Minimum And 1.843 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Distance Between Mounting Hole Centers:	1.377 Inches Minimum And 1.407 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.712 Inches Minimum And 0.742 Inches Maximum
Inside Diameter/arch Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D10T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.