

Description

NAS1716D12K Loop Clamp

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D12K
Minimum Qty (MOQ):	5
NSN:	5340-01-019-2977
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N NAS1716D12K Specifications

Overall Length:	1.938 Inches Minimum And 1.968 Inches Maximum
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Distance Between Mounting Hole Centers:	1.502 Inches Minimum And 1.532 Inches Maximum
Cushioning Material:	Plastic, Polytetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.837 Inches Minimum And 0.867 Inches Maximum
Inside Diameter/arch Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D12K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.