

Description

Length: 2-1/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D14K
Minimum Qty (MOQ):	1 EA
NSN:	5340-01-398-1289
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1716D14K Specifications

Overall Length:	2.0780 Inches Nominal
Overall Width:	0.5000 Inches Nominal
Material Thickness:	0.0400 Inches Nominal
Distance Between Mounting Hole Centers:	1.6270 Inches Minimum And 1.6570 Inches Maximum
Cushioning Material:	Plastic, Polytetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Inside Diameter/arch Length:	0.8600 Inches Minimum And 0.8900 Inches Maximum
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D14K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.