

**Description**

Saddle Cushioned Clamp part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D17K
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-256-3203
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE  
AVAILABLE

## P/N NAS1716D17K Specifications

<b>Overall Length:</b>	2.337 Inches Nominal
<b>Overall Width:</b>	0.620 Inches Nominal
<b>Material Thickness:</b>	0.620 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	1.822 Inches Minimum And 1.852 Inches Maximum
<b>Cushioning Material:</b>	Plastic, Polytetrafluoroethylene
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	1.047 Inches Minimum And 1.077 Inches Maximum
<b>Inside Diameter/arch Length:</b>	1.047 Inches Minimum And 1.077 Inches Maximum
<b>Material:</b>	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
<b>Material:</b>	Aluminum Alloy 2024 And Aluminum Alloy 1230
<b>Style Designator:</b>	Saddle Arch
<b>Specification/standard Data:</b>	80205-nas1716 Professional/Industrial Association Standard

## How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D17K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.