

**Description**

Length: 2-17/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1716D20K
Minimum Qty (MOQ):	2
NSN:	5340-01-166-2694
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



\* See page 2 for technical characteristics

# P/N NAS1716D20K Specifications

Overall Length:	2.539 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.024 Inches Minimum And 2.054 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.374 Inches Nominal
Inside Diameter/arch Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1716 Professional/industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D20K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.