

P/N NAS1716D24T

Description

Length: 2-25/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1716D24T

Minimum Qty (MOQ): 5 EA

NSN: 5340-00-124-9228

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip



^{*} See page 2 for technical characteristics

P/N NAS1716D24T Specifications

Overall Length:	2.789 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.274 Inches Minimum And 2.304 Inches Maximum
Cushioning Material:	Plastic, Polytetrafluoroethylene And Plastic, Tetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.624 Inches Nominal
Inside Diameter/arch Length:	1.500 Inches Nominal
Material:	Aluminum Alloy, Qq-a-250/5
Material:	Aluminum Alloy 2024
Style Designator:	Saddle Arch

How to Order

Order this saddle cushioned clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/NAS1716D24T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1716D24T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1716D24T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/NAS1716D24T and selecting the quantity you want then click "add to cart".