

Description

Length: 2-25/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D24T
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-124-9228
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1716D24T Specifications

Overall Length:	2.789 Inches Nominal
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.274 Inches Minimum And 2.304 Inches Maximum
Cushioning Material:	Plastic, Polytetrafluoroethylene And Plastic, Tetrafluoroethylene
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.624 Inches Nominal
Inside Diameter/arch Length:	1.500 Inches Nominal
Material:	Aluminum Alloy, Qq-a-250/5
Material:	Aluminum Alloy 2024
Style Designator:	Saddle Arch

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D24T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.