

**Description**

Length: 3-19/64",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D32K
Minimum Qty (MOQ):	2
NSN:	5340-00-240-3511
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

## P/N NAS1716D32K Specifications

<b>Overall Length:</b>	3.274 Inches Minimum And 3.304 Inches Maximum
<b>Overall Width:</b>	0.620 Inches Nominal
<b>Material Thickness:</b>	0.062 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	2.774 Inches Minimum And 2.804 Inches Maximum
<b>Cushioning Material:</b>	Plastic, Ams 3651
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	2.139 Inches Nominal
<b>Inside Diameter/arch Length:</b>	1.985 Inches Minimum And 2.015 Inches Maximum
<b>Material:</b>	Aluminum Alloy,qq-a-250/5,alloy Alclad 2024,t4 Or T42
<b>Material:</b>	Aluminum Alloy,qq-a-250/5,alloy Alclad 2024,t4 Or T42
<b>Style Designator:</b>	Saddle Arch
<b>Specification/standard Data:</b>	80205-nas1711 Professional/Industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D32K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.