

## Description

Length: 3-19/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1716D32K
Minimum Qty (MOQ):	2
NSN:	5340-00-240-3511
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

# P/N NAS1716D32K Specifications

Overall Length:	3.274 Inches Minimum And 3.304 Inches Maximum
Overall Width:	0.620 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	2.774 Inches Minimum And 2.804 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	2.139 Inches Nominal
Inside Diameter/arch Length:	1.985 Inches Minimum And 2.015 Inches Maximum
Material:	Aluminum Alloy,qq-a-250/5,alloy Alclad 2024,t4 Or T42
Material:	Aluminum Alloy,qq-a-250/5,alloy Alclad 2024,t4 Or T42
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1711 Professional/industrial Association Standard

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D32K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.