

Description

Saddle Cushioned Clamp part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1716D50K
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-196-3583
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1716D50K Specifications

Overall Length:	4.399 Inches Minimum And 4.429 Inches Maximum
Overall Width:	0.625 Inches Nominal
Material Thickness:	0.062 Inches Nominal
Distance Between Mounting Hole Centers:	3.899 Inches Minimum And 3.929 Inches Maximum
Cushioning Material:	Plastic, Ams 3651
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	3.234 Inches Minimum And 3.264 Inches Maximum
Inside Diameter/arch Length:	3.110 Inches Minimum And 3.140 Inches Maximum
Material:	Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4
Material:	Aluminum Alloy 2024 And Aluminum Alloy 1230
Style Designator:	Saddle Arch
Specification/standard Data:	80205-nas1716 Professional/Industrial Association Standard

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D50K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.