

Description

Length: 4-13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | NAS1716D50T |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-247-5700 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N NAS1716D50T Specifications

| | |
|---|---|
| Overall Length: | 4.414 Inches Nominal |
| Overall Width: | 0.620 Inches Nominal |
| Material Thickness: | 0.062 Inches Nominal |
| Distance Between Mounting Hole Centers: | 3.899 Inches Minimum And 3.929 Inches Maximum |
| Cushioning Material: | Plastic, Ams 3651 |
| Cushion: | Included |
| Mounting Pad: | Not Included |
| Mounting Hole Size: | 0.204 Inches Nominal |
| Distance Between Base And Inside Of Arch: | 3.249 Inches Nominal |
| Inside Diameter/arch Length: | 3.110 Inches Minimum And 3.130 Inches Maximum |
| Material: | Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T4 Or Aluminum Alloy, Qq-a-250/5, Alloy Alclad 2024, T42 |
| Material: | Aluminum Alloy 2024 And Aluminum Alloy 1230 Or Aluminum Alloy 2024 And Aluminum Alloy 1230 |
| Style Designator: | Saddle Arch |
| Specification/standard Data: | 80205-nas1716 Professional/industrial Association Standard |

How to Order

Order this saddle cushioned clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1716D50T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.