

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1719H4L2A
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-552-3282
Schedule B:	7616.10.9090
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1719H4L2A Specifications

Fastener Length:	0.390 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.050 Inches Minimum And 0.141 Inches Maximum
Shear Strength:	450 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Stem Or Mil-c-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1719 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1719H4L2A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.