

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1719H5L4A |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-552-3286 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N NAS1719H5L4A Specifications

| | |
|---|--|
| Fastener Length: | 0.650 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.196 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.172 Inches Minimum And 0.266 Inches Maximum |
| Shear Strength: | 450 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Aluminum Alloy 7075 Stem |
| Material: | Aluminum Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Stem Or Mil-c-5541 Mil Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1719 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1719H5L4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.