

Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1719H5L4A
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-552-3286
Schedule B:	7616.10.3000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1719H5L4A Specifications

<b>Fastener Length:</b>	0.650 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.196 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.172 Inches Minimum And 0.266 Inches Maximum
<b>Shear Strength:</b>	450 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Aluminum Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Stem Or Mil-c-5541 Mil Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas1719 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1719H5L4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.