

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1720C4L3P |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-580-6671 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1720C4L3P Specifications

| | |
|---|--|
| Fastener Length: | 0.325 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.059 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.129 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.245 Inches Minimum And 0.255 Inches Maximum |
| Grip Length: | 0.109 Inches Minimum And 0.203 Inches Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5734 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Stem |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1720 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720C4L3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.