

**Description**

Mbc Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1720C4L4W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-573-2756
Schedule B:	7318.23.0000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1720C4L4W Specifications

<b>Fastener Length:</b>	0.348 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.059 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.129 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.245 Inches Minimum And 0.255 Inches Maximum
<b>Grip Length:</b>	0.172 Inches Minimum And 0.266 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5734 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2, CI 2 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1720 Professional/industrial Association Standard

## How to Order

Order this mbc rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720C4L4W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.