

## **P/N NAS1720C4L5P**

### **Description**

Mbc Rivet part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1720C4L5P
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-590-2108
Schedule B:	7318.23.0000
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1720C4L5P Specifications

Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.072 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.177 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.307 Inches Minimum And 0.317 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
Grip Length:	0.234 Inches Minimum And 0.328 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Surface Treatment:	Passivate Overall

## **How to Order**

Order this mbc rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1720C4L5P">https://military-fasteners.com/rivets/blind+rivets/NAS1720C4L5P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.