

Description

Mbc Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1720C5L3W
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-573-2741
Schedule B:	7318.16.0060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1720C5L3W Specifications

Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.072 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.177 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.307 Inches Minimum And 0.317 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
Grip Length:	0.109 Inches Minimum And 0.203 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5734 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2, Cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1720 Professional/industrial Association Standard

How to Order

Order this mbc rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720C5L3W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.