

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1720C5L4P
Minimum Qty (MOQ):	10
NSN:	5320-01-590-2133
Schedule B:	7318.23.0000
ECCN:	EAR99



\* See page 2 for technical characteristics

# P/N NAS1720C5L4P Specifications

Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.072 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.177 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.307 Inches Minimum And 0.317 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
Grip Length:	0.172 Inches Minimum And 0.266 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Surface Treatment:	Passivate Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720C5L4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.