

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1720C5L6P
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-590-3402
Schedule B:	7318.23.0000
ECCN:	EAR99



## P/N NAS1720C5L6P Specifications

<b>Head Style:</b>	Flat Chamfer
<b>Head Height:</b>	0.067 Inches Minimum And 0.072 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.297 Inches Minimum And 0.391 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Blind, Protruding Head,mechanically Locked Spindle
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720C5L6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.