

## **P/N NAS1720H4L2A**

### **Description**

NAS1720 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1720H4L2A

Minimum Qty (MOQ): 20

NSN: 5320-01-506-4072

Schedule B: 7616.10.3000

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1720H4L2A Specifications

Fastener Length:	0.263 Inches Maximum
Head Style:	Universal
Head Height:	0.049 Inches Minimum And 0.059 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.047 Inches Minimum And 0.141 Inches Maximum
Material:	Aluminum Alloy Sleeve

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1720H4L2A">https://military-fasteners.com/rivets/blind+rivets/NAS1720H4L2A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.